



Project No.: TM-2206000658P
Report No.: TMXD2206003112DE

Page: 1 / 37
Rev.: 00

FCC TEST REPORT

for

UP 4000 Board; UP 4000 Edge

MODEL: xUPxAPL03x (x - Where x may be any combination of alphanumeric characters or "-" or blank.); xUPxEDGExAPL03x (x - Where x may be any combination of alphanumeric characters or "-" or blank.)

Issued to:

AAEON Technology Inc.

**5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist.,
New Taipei City, Taiwan, R.O.C.**

Issued by:

Compliance Certification Services Inc.

Xindian Lab.

**No.163-1, Jhongsheng Rd., Xindian Dist.,
New Taipei City, Taiwan.**

TEL: 886-2-22170894

FAX: 886-2-22171029

Issued Date: August 15, 2022

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMXD2206003112DE

Page: 2 / 37
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	August 15, 2022	Initial Issue	ALL	Linda Wu



TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION.....	4
2	EUT DESCRIPTION.....	5
3	TEST METHODOLOGY.....	6
3.1.	DECISION OF FINAL TEST MODE.....	6
3.2.	EUT SYSTEM OPERATION	6
4	SETUP OF EQUIPMENT UNDER TEST	7
4.1.	DESCRIPTION OF SUPPORT UNITS.....	7
4.2.	CONFIGURATION OF SYSTEM UNDER TEST.....	8
5	FACILITIES AND ACCREDITATIONS	9
5.1.	FACILITIES	9
5.2.	ACCREDITATIONS.....	9
5.3.	MEASUREMENT UNCERTAINTY	9
6	CONDUCTED EMISSION MEASUREMENT	10
6.1.	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	10
6.2.	TEST INSTRUMENTS	10
6.3.	TEST PROCEDURES.....	11
6.4.	TEST SETUP	12
6.5.	DATA SAMPLE	12
6.6.	TEST RESULTS	13
7	RADIATED EMISSION MEASUREMENT	15
7.1.	LIMITS OF RADIATED EMISSION MEASUREMENT	15
7.2.	TEST INSTRUMENTS	17
7.3.	TEST PROCEDURES.....	18
7.4.	TEST SETUP	19
7.5.	DATA SAMPLE	20
7.6.	TEST RESULTS	21
8	PHOTOGRAPHS OF THE TEST CONFIGURATION	26
	APPENDIX 1 - PHOTOGRAPHS OF EUT	29

1 TEST RESULT CERTIFICATION

Product: UP 4000 Board; UP 4000 Edge

Model: xUPxAPL03x (x - Where x may be any combination of alphanumeric characters or "-" or blank.); xUPxEDGEAPL03x (x - Where x may be any combination of alphanumeric characters or "-" or blank.)

Brand: AAEON

Applicant: AAEON Technology Inc.
5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist.,
New Taipei City, Taiwan, R.O.C.

Manufacturer: AAEON Technology Inc.
5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist.,
New Taipei City, Taiwan, R.O.C.

Tested: July 16, 2022 ~ August 4, 2022


EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7-2020 ANSI C63.4-2014	Conducted (Power Port)	PASS	Meet Class A limit
	Radiated	PASS	Meet Class A limit

Statements of Conformity

Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.


The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Sam Hu
Assistant Manager

Reviewed by:



Eva Fan
Supervisor of report document dept.

2 EUT DESCRIPTION

Product	UP 4000 Board; UP 4000 Edge
Brand Name	AAEON
Model	xUPxAPL03x (x - Where x may be any combination of alphanumeric characters or "-"or blank.); xUPxEDGEExAPL03x (x - Where x may be any combination of alphanumeric characters or "-"or blank.)
Applicant	AAEON Technology Inc.
Housing material	UP 4000 Board: N/A UP 4000 Edge: Metal case
Received Date	June 30, 2022
EUT Power Rating	12VDC from Adaptor
AC Power During Test	120VAC / 60Hz & 230VAC / 60Hz to Adaptor
AC Adaptor Manufacturer	Powertron Electronic Corp.
AC Adaptor Model Number	PS1065-120IB500
AC Adaptor Power Rating	I/P: 100-240VAC~50-60Hz, 1.8A O/P: 12VDC, 5.0A 60W
DC Power Cable Type	Unshielded, 1.0m (Non-detachable, with two cores)

Model Differences

Model	Difference		Tested (Checked)
UP-APL03	EUT 1	UP 4000 Board	<input checked="" type="checkbox"/>
	EUT 2	Power Button Difference	<input checked="" type="checkbox"/>
UP-EDGE-APL03	EUT 1	UP 4000 Edge	<input checked="" type="checkbox"/>
	EUT 2	Power Button Difference	<input checked="" type="checkbox"/>
xUPxAPL03x; xUPxEDGEExAPL03x	1. x - Where x may be any combination of alphanumeric characters or "-"or blank. 2. For marketing purpose only.		<input type="checkbox"/>

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
1. HDMI Port	1	1
2. Earphone Port	1	1
3. Microphone Port	1	1
4. USB 3.0 Port	3	3
5. USB Type-C Port	1	1
6. LAN Port	1	1

Note: Client consigns only one model sample to test (Model Number: UP-APL03; UP-EDGE-APL03).

3 TEST METHODOLOGY**3.1. DECISION OF FINAL TEST MODE**

The EUT was tested together with the below additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The test configuration/ modes are as the following:

Conduction Modes:

1	EUT 1	HDMI 3840*2160, 30Hz	120VAC, 60Hz
2			230VAC, 60Hz

Radiation Modes:

1	EUT 1	HDMI 3840*2160, 30Hz	120VAC, 60Hz
		HDMI 3840*2160, 30Hz / 1-12.5GHz	
2		HDMI 3840*2160, 30Hz	230VAC, 60Hz
3	EUT 2	HDMI 3840*2160, 30Hz	120VAC, 60Hz

Worst:

Conduction: Mode 1

Radiation: Mode 1

3.2. EUT SYSTEM OPERATION

1. Windows 10 boots system.
2. Run Burnintest.exe to activate all peripherals and display "H" pattern on monitor screen.
3. Run Lantest20.exe to ping 192.168.1.149 -t (EUT), ping 192.168.1.99 -t (Server PC).

Note: Test program is self-repeating throughout the test.

4 SETUP OF EQUIPMENT UNDER TEST

4.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

EUT Devices:

No.	Equipment	Model No.	Brand Name
1	CPU (2.5GHz)	CPU.Apollo Lake.Pentium	Intel
2	Memory (2GB LPDDR4) *4	MT53D512M32D2DS-053	Micron
3	Power Adapter	PS1065-120IB500	Powertron
4	eMMC (64GB)	SDINBDA4-64G-V	Sandisk


Peripherals Devices:

No.	Equipment	Model No.	Serial No.	FCC ID / BSMI ID	Brand Name	Data Cable	Power Cord
1	Earphone & Microphone	X710	N/A	N/A	HAWK	Unshielded, 1.8m	N/A
2	USB Mouse	M-U0026	N/A	BSMI: T41126	LOGITECT	Shielded, 1.8m	N/A
3	USB Keyboard	Y-U0011	1804SY04FP48	BSMI: D51160	LOGITECH	Shielded, 1.8m	N/A
4	USB HDD	SE730	110420099649	D33A23	ADATA	Shielded, 0.3m	N/A
5	USB HDD	TS1TSJ25MC	N/A	BSMI: D33193	Transcend	Shielded, 0.3m	N/A
6	Monitor	PA248Q	G5LMQS071288	BSMI: R31018	ASUS	Shielded, 1.8m	Unshielded, 1.8m
7	Server PC	T3610	57TT032	BSMI: R33002	DELL	Unshielded, 20m	Unshielded, 1.8m

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2. CONFIGURATION OF SYSTEM UNDER TEST



5 FACILITIES AND ACCREDITATIONS

5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at CCSrf Taiwan Xindian Lab. at No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Japan	VCCI
Taiwan	BSMI
USA	FCC

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	0.15MHz ~ 30MHz	± 2.8
Radiated emissions	30MHz ~ 1000MHz	± 5.1
	1000MHz ~ 18000MHz	± 4.6
	18000MHz ~ 40000MHz	± 3.8

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22: 2005, clause 11, Measurement Uncertainty) determining compliance with the limits shall be based on the results of the compliance measurement. Consequently the measured emissions being less than the maximum allowed emission result in this being a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is based on conducted and radiated emissions being less than U_{CISPR} which is 3.8dB(AMN); 5.2dB(OATS) and 5.5dB(1-18GHz) respectively. CCS values (called U_{Lab} in CISPR 16-4-2) is less than U_{CISPR} as shown in the table above. Therefore, MU need not be considered for compliance.

6 CONDUCTED EMISSION MEASUREMENT

6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

6.2. TEST INSTRUMENTS

Conducted Emission room # B				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Attenuator	MCL	HAT-10	SD-C012	03/21/2023
BNC Cable	EMEC	CFD300-NL	SD-C020	01/03/2023
EMI Test Receiver	R&S	ESR3	102166	03/27/2023
LISN	Schwarzbeck	NSLK 8127	8127382	04/05/2023
LISN(EUT)	Schwarzbeck	NSLK 8127	8127526	04/05/2023
Thermo-Hygro Meter	Wisewind	N/A	SD-S017	09/01/2022
Test S/W	EZ-EMC			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

6.3. TEST PROCEDURES


Procedure of Preliminary Test

- The EUT and support equipment, if needed, were set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- The test equipment EUT installed by AC main power, through a Line Impedance Stabilization Network (LISN), which was supplied power source and was grounded to the ground plane.
- All support equipment power by from a second LISN.
- The test program of the EUT was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- The test data of the worst-case condition(s) was recorded.

6.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

6.5. DATA SAMPLE

Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
x.xx	42.95	0.55	43.50	73	-29.50	Q	L1


Freq. = Emission frequency in MHz
 Reading = Uncorrected Analyzer/Receiver reading
 Factor = Insertion loss of LISN + Cable Loss + Pulse Limit
 Result = Reading + Factor
 Limit = Limit stated in standard
 Margin = Reading in reference to limit
 P = Peak Reading
 Q = Quasi-peak Reading
 A = Average Reading
 L1 = Hot side
 L2 = Neutral side

Calculation Formula

Margin (dB) = Result (dBuV) – Limit (dBuV)

6.6. TEST RESULTS


Model No.	UP-APL03; UP-EDGE-APL03	6dB Bandwidth	9 kHz
Environmental Conditions	23.9°C, 58% RH	Test Mode	Mode 1
Tested by	Alee Shen	Phase	L1
Standard	FCC CLASS A / ICES-003 CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1500	38.90	10.08	48.98	79.00	-30.02	P	L1
0.1770	36.54	10.08	46.62	79.00	-32.38	P	L1
0.2445	29.67	10.08	39.75	79.00	-39.25	P	L1
2.2020	29.58	10.29	39.87	73.00	-33.13	P	L1
5.8560	31.89	10.41	42.30	73.00	-30.70	P	L1
8.5290	27.96	10.46	38.42	73.00	-34.58	P	L1

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Model No.	UP-APL03; UP-EDGE-APL03	6dB Bandwidth	9 kHz
Environmental Conditions	23.9°C, 58% RH	Test Mode	Mode 1
Tested by	Alee Shen	Phase	L2
Standard	FCC CLASS A / ICES-003 CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1500	40.08	10.09	50.17	79.00	-28.83	P	L2
0.4785	28.46	10.13	38.59	79.00	-40.41	P	L2
2.0400	30.56	10.27	40.83	73.00	-32.17	P	L2
5.8425	31.05	10.38	41.43	73.00	-31.57	P	L2
13.5645	23.57	10.56	34.13	73.00	-38.87	P	L2
29.1120	19.29	10.90	30.19	73.00	-42.81	P	L2

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

7 RADIATED EMISSION MEASUREMENT

7.1. LIMITS OF RADIATED EMISSION MEASUREMENT

FCC 47 CFR Part 15 Subpart B

Below 1GHz (for digital device)

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHZ)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

NOTE: (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
 (3) The measurement above 1GHz is at close-in distances 3m, and determine the limit **L2** corresponding to the close-in distance **d2** by applying the following relation: **L2 = L1 (d1/d2)**, where **L1** is the specified limit in microvolts per metre (**uV/m**) at the distance **d1 (10m)**, **L2** is the new limit for distance **d2 (3m)**.
 So the new Class A limit above 1GHz at 3m is as following table:

Frequency (MHZ)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80

According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

ICES-003 Issue 7-2020

Below 1GHz

Class A Radiated Emission limit

Frequency (MHZ)	(dBuV/m)Q.P. Distances (3m)	(dBuV/m)Q.P. Distances (10m)
30 - 88	50	40
88 - 216	54	43.5
216 - 230	56.9	46.4
230 - 960	57	47
960 - 1000	60	49.5

Class B Radiated Emission limit

Frequency (MHZ)	(dBuV/m)Q.P. Distances (3m)	(dBuV/m)Q.P. Distances (10m)
30 - 88	40	30
88 - 216	43.5	33.1
216 - 230	46	35.6
230 - 960	47	37
960 - 1000	54	43.5

Above 1GHz

Frequency (MHZ)	Class A (dBuV/m) (At 3m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	60	80	54	74

Required highest measurement frequency for radiated emissions

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Fx-108	1000
108-500	2000
500-1000	5000
Above 1000	5 x FX up to a maximum of 40 GHz

Note: Fx is the highest fundamental frequency generated and/or used in the ITE or digital apparatus under test.

7.2. TEST INSTRUMENTS

Open Area Test Site # H				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Bilog Antenna	Teseq	CBL 6112D	40529	09/22/2022
Cable	EMEC	CFD400E-LW	SD-R074	08/11/2022
EMI Test Receiver	R&S	ESCI	101340	02/10/2023
Pre-Amplifier	HP	8447D	1937A01554	09/23/2022
Thermo-Hygro Meter	Wisewind	201A	No. 03	05/17/2023
Test S/W	EZ-EMC			
Chamber # E (Above 1GHz Used)				
Horn Antenna	ETS	3117	00078732	10/24/2022
K-Type Cable x 1m (1-40GHz)	EMCI	EMC101G-KM-KM-1000	SD-R069	10/25/2022
Microflex Cable x 7m	EMCI	EMC106-SM-NM-7000	SD-R056	10/25/2022
Pre-Amplifier	HP	8449B	3008A01266	10/25/2022
Signal Analyzer	Agilent	N9010A	MY53440125	10/25/2022
Thermo-Hygro Meter	Wisewind	201A	SD-R046	08/09/2022
Test S/W	EZ-EMC			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

7.3. TEST PROCEDURES

Procedure of Preliminary Test


- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test


- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 or 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.

7.4. TEST SETUP

Below 1GHz



Above 1GHz



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.5. DATA SAMPLE

Below 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/Q)	Pol. (H/V)
x.xx	14.0	12.2	26.2	40	-13.8	Q	H

Above 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
x.xx	42.95	0.55	43.50	60	-16.50	A	H

Freq. = Emission frequency in MHz
 Reading = Uncorrected Analyzer/Receiver reading
 Factor = Antenna Factor + Cable Loss - Amplifier Gain
 Result = Reading + Factor
 Limit = Limit stated in standard
 Margin = Reading in reference to limit
 P = Peak Reading
 Q = Quasi-peak Reading
 A = Average Reading
 H = Antenna Polarization: Horizontal
 V = Antenna Polarization: Vertical

Calculation Formula


Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

7.6. TEST RESULTS

FCC 47 CFR Part 15 Subpart B

Below 1GHz


Model No.	UP-APL03; UP-EDGE-APL03	Test Mode	Mode 1
Environmental Conditions	31°C, 58% RH	6dB Bandwidth	120 kHz
Antenna Pole	Vertical	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Alee Shen
Standard	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		



Radiated Emission Readings									
Frequency Range Investigated				30 MHz to 1000 MHz at 10m					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
51.2200	42.90	-13.34	29.56	40.00	-10.44	100	116	Q	V
75.0600	41.60	-13.98	27.62	40.00	-12.38	100	254	Q	V
240.0600	39.80	-8.18	31.62	47.00	-15.38	100	180	Q	V
297.0500	38.70	-6.09	32.61	47.00	-14.39	100	231	Q	V
890.0100	32.10	3.95	36.05	47.00	-10.95	400	198	Q	V
990.0600	30.10	4.95	35.05	47.00	-11.95	400	207	Q	V

Note: 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.
2. P= Peak Reading; Q= Quasi-peak Reading.

Model No.	UP-APL03; UP-EDGE-APL03	Test Mode	Mode 1
Environmental Conditions	31°C, 58% RH	6dB Bandwidth	120 kHz
Antenna Pole	Horizontal	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Alee Shen
Standard	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		




Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
35.1800	34.00	-5.04	28.96	40.00	-11.04	400	90	Q	H
297.0150	43.60	-6.09	37.51	47.00	-9.49	400	244	Q	H
594.2199	30.10	0.53	30.63	47.00	-16.37	100	178	Q	H
792.0600	28.70	2.94	31.64	47.00	-15.36	100	44	Q	H
890.3310	31.20	3.97	35.17	47.00	-11.83	100	132	Q	H
990.1200	28.50	4.95	33.45	47.00	-13.55	100	110	Q	H

Note: 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.
2. P= Peak Reading; Q= Quasi-peak Reading.

ICES-003 Issue 7-2020

Below 1GHz


Model No.	UP-APL03; UP-EDGE-APL03	Test Mode	Mode 1
Environmental Conditions	31°C, 58% RH	6dB Bandwidth	120 kHz
Antenna Pole	Vertical	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Alee Shen
Standard	ICES-003 CLASS A		



Radiated Emission Readings									
Frequency Range Investigated				30 MHz to 1000 MHz at 10m					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
51.2200	42.90	-13.34	29.56	40.00	-10.44	100	116	Q	V
75.0600	41.60	-13.98	27.62	40.00	-12.38	100	254	Q	V
240.0600	39.80	-8.18	31.62	47.00	-15.38	100	180	Q	V
297.0500	38.70	-6.09	32.61	47.00	-14.39	100	231	Q	V
890.0100	32.10	3.95	36.05	47.00	-10.95	400	198	Q	V
990.0600	30.10	4.95	35.05	49.50	-14.45	400	207	Q	V

Note: 1. P= Peak Reading; Q= Quasi-peak Reading.

Model No.	UP-APL03; UP-EDGE-APL03	Test Mode	Mode 1
Environmental Conditions	31°C, 58% RH	6dB Bandwidth	120 kHz
Antenna Pole	Horizontal	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Alee Shen
Standard	ICES-003 CLASS A		



Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
35.1800	34.00	-5.04	28.96	40.00	-11.04	400	90	Q	H
297.0150	43.60	-6.09	37.51	47.00	-9.49	400	244	Q	H
594.2199	30.10	0.53	30.63	47.00	-16.37	100	178	Q	H
792.0600	28.70	2.94	31.64	47.00	-15.36	100	44	Q	H
890.3310	31.20	3.97	35.17	47.00	-11.83	100	132	Q	H
990.1200	28.50	4.95	33.45	49.50	-16.05	100	110	Q	H

Note: 1. P= Peak Reading; Q= Quasi-peak Reading.

Above 1GHz

Model No.	UP-APL03; UP-EDGE-APL03	Test Mode	Mode 1
Environmental Conditions	25.6°C, 62% RH	6dB Bandwidth	1 MHz
Antenna Pole	Vertical / Horizontal	Antenna Distance	3m
Highest frequency generated or used	2500MHz	Upper frequency	12500MHz
Detector Function	Peak and average.	Tested by	Alee Shen
Standard	FCC CLASS A / ICES-003 CLASS A		

Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1136.000	49.52	-7.85	41.67	80.00	-38.33	P	V
1408.000	50.26	-8.03	42.23	80.00	-37.77	P	V
1765.000	52.28	-6.20	46.08	80.00	-33.92	P	V
2394.000	48.49	-4.27	44.22	80.00	-35.78	P	V
2564.000	48.48	-4.05	44.43	80.00	-35.57	P	V
3278.000	47.20	-3.49	43.71	80.00	-36.29	P	V

Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1170.000	49.89	-7.85	42.04	80.00	-37.96	P	H
1476.000	53.37	-8.67	44.70	80.00	-35.30	P	H
1765.000	49.72	-6.20	43.52	80.00	-36.48	P	H
2071.000	48.67	-5.11	43.56	80.00	-36.44	P	H
2564.000	51.08	-4.05	47.03	80.00	-32.97	P	H
2768.000	46.28	-4.06	42.22	80.00	-37.78	P	H



Note: 1. P= Peak Reading; A= Average Reading.


8 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST




RADIATED EMISSION TEST (Below 1GHz)

RADIATED EMISSION TEST (Above 1GHz)





APPENDIX 1 - PHOTOGRAPHS OF EUT**EUT 1**









EUT 2

