



Report No.: T200702D02-D

Ref. No.: T191101D05-D

Page: 1 / 25  
Rev.: 01

## FCC TEST REPORT

for

**(1)UP Xtreme Board (2)UP Xtreme Edge computing system (3)AI Core X**

**MODEL: (1)xUPxWHLx(x – where x may be any combination of alphanumeric characters or “-” or blank) (2)xUPxEDGE(x – where x may be any combination of alphanumeric characters or “-” or blank) (3)xPERxTAIX(x – where x may be any combination of alphanumeric characters or “-” or blank) (4)xUPxISHx(x – where x may be any combination of alphanumeric characters or “-” or blank)**

Issued to:

**AAEON Technology Inc.**

**5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist.,  
New Taipei City, Taiwan, R.O.C**

Issued by:

**Compliance Certification Services Inc.**

**Xindian Lab.**

**No.163-1, Jhongsheng Rd., Xindian Dist.,  
New Taipei City, Taiwan.**

**TEL: 886-2-22170894**

**FAX: 886-2-22171029**

**Issued Date: July 13, 2020**

**Note:** This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



**Report No.:** T200702D02-D

**Ref. No.:** T191101D05-D

Page: 2 / 25  
Rev.: 01

**Revision History**

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	November 22, 2019	Initial Issue	ALL	Linda Wu
01	July 13, 2020	Add Model	ALL	Linda Wu



Report No.: T200702D02-D

Ref. No.: T191101D05-D

Page: 3 / 25  
Rev.: 01

## TABLE OF CONTENTS

<b>1</b>	<b>TEST RESULT CERTIFICATION.....</b>	<b>4</b>
<b>2</b>	<b>EUT DESCRIPTION.....</b>	<b>5</b>
<b>3</b>	<b>TEST METHODOLOGY.....</b>	<b>7</b>
3.1.	DECISION OF FINAL TEST MODE.....	7
3.2.	EUT SYSTEM OPERATION.....	7
<b>4</b>	<b>SETUP OF EQUIPMENT UNDER TEST.....</b>	<b>8</b>
4.1.	DESCRIPTION OF SUPPORT UNITS.....	8
4.2.	CONFIGURATION OF SYSTEM UNDER TEST.....	9
<b>5</b>	<b>FACILITIES AND ACCREDITATIONS.....</b>	<b>10</b>
5.1.	FACILITIES.....	10
5.2.	ACCREDITATIONS.....	10
5.3.	MEASUREMENT UNCERTAINTY.....	10
<b>6</b>	<b>CONDUCTED EMISSION MEASUREMENT.....</b>	<b>11</b>
6.1.	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	11
6.2.	TEST INSTRUMENTS.....	11
6.3.	TEST PROCEDURES.....	12
6.4.	TEST SETUP.....	13
6.5.	DATA SAMPLE.....	13
6.6.	TEST RESULTS.....	14
<b>7</b>	<b>RADIATED EMISSION MEASUREMENT.....</b>	<b>16</b>
7.1.	LIMITS OF RADIATED EMISSION MEASUREMENT.....	16
7.2.	TEST INSTRUMENTS.....	17
7.3.	TEST PROCEDURES.....	18
7.4.	TEST SETUP.....	19
7.5.	DATA SAMPLE.....	20
7.6.	TEST RESULTS.....	21
<b>8</b>	<b>PHOTOGRAPHS OF THE TEST CONFIGURATION.....</b>	<b>24</b>
	<b>APPENDIX 1 - PHOTOGRAPHS OF EUT.....</b>	<b>A1-1</b>

# 1 TEST RESULT CERTIFICATION

**Product:** (1)UP Xtreme Board (2)UP Xtreme Edge computing system (3)AI Core X

**Model:** (1)xUPxWHLx(x – where x may be any combination of alphanumeric characters or “-” or blank) (2)xUPXxEDGEx(x – where x may be any combination of alphanumeric characters or “-” or blank) (3)xPERxTAIXx(x – where x may be any combination of alphanumeric characters or “-” or blank) (4)xUPXxISHx(x – where x may be any combination of alphanumeric characters or “-” or blank)

**Brand:** AAEON

**Applicant:** **AAEON Technology Inc.**  
5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist.,  
New Taipei City, Taiwan, R.O.C

**Manufacturer:** **AAEON Technology Inc.**  
5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist.,  
New Taipei City, Taiwan, R.O.C

**Tested:** November 5, 2019 ~ November 6, 2019


EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 6-2016 ANSI C63.4-2014	Conducted (Power Port)	PASS	Meet Class A limit
	Radiated	PASS	Meet Class A limit

## Statements of Conformity

Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.


The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Sam Hu  
Assistant Manager

Reviewed by:



Eva Fan  
Supervisor of report document dept.

## 2 EUT DESCRIPTION

<b>Product</b>	(1)UP Xtreme Board (2)UP Xtreme Edge computing system (3)AI Core X
<b>Brand Name</b>	AAEON
<b>Model</b>	(1)xUPxWHLx(x – where x may be any combination of alphanumeric characters or “-” or blank) (2)xUPXxEDGEx(x – where x may be any combination of alphanumeric characters or “-” or blank) (3)xPERxTAIXx(x – where x may be any combination of alphanumeric characters or “-” or blank) (4)xUPXxISHx(x – where x may be any combination of alphanumeric characters or “-” or blank)
<b>Applicant</b>	AAEON Technology Inc.
<b>Housing material</b>	Metal case
<b>Identify Number</b>	T191101D05
<b>Received Date</b>	November 1, 2019
<b>EUT Power Rating</b>	19VDC from AC Adaptor
<b>AC Power During Test</b>	120VAC / 60Hz & 230VAC / 60Hz to AC Adaptor
<b>AC Adaptor Manufacturer</b>	GEAO
<b>AC Adaptor Model Number</b>	GEO651DA-190342
<b>AC Adaptor Power Rating</b>	I/P:100-240VAC~50/60Hz, 1.5A O/P: 19VDC, 3.42A
<b>DC Power Cable Type</b>	Unshielded, 1.5m (Non-detachable, with a core)

**Model Differences**

Model Name	Difference	Tested (Checked)
UPX-WHL01	UP Xtreme Board	<input checked="" type="checkbox"/>
xUPxWHLx	1. x – where x may be any combination of alphanumeric characters or “-” or blank. 2. For marketing purpose only.	<input type="checkbox"/>
UPX-EDGE	UP Xtreme Edge computing system	<input checked="" type="checkbox"/>
xUPXxEDGEEx	1. x – where x may be any combination of alphanumeric characters or “-” or blank. 2. For marketing purpose only.	<input type="checkbox"/>
PER-TAIX2-A20-2280	AI Core X	<input checked="" type="checkbox"/>
xPERxTAIXx	1. x – where x may be any combination of alphanumeric characters or “-” or blank. 2. For marketing purpose only.	<input type="checkbox"/>
xUPXxISHx	1. x – where x may be any combination of alphanumeric characters or “-” or blank. 2. For marketing purpose only to xUPxWHLx.	<input type="checkbox"/>

**I/O PORT**

I/O PORT TYPES	Q'TY	TESTED WITH
1. COM Port	2	2
2. HDMI Port	1	1
3. Display Port	1	1
4. Audio Play	1	1
5. USB Port	4	4
6. LAN Port	2	2

**Note:** Client consigns only one model sample to test (Model Number: UPX-WHL01; UPX-EDGE; PER-TAIX2-A20-2280).

### 3 TEST METHODOLOGY

#### 3.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the below additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The test configuration modes are as the following:

**Conduction Modes:**

1	HDMI+DP Mode 1920X1080, VF=60Hz	120VAC, 60Hz
2		230VAC, 60Hz

**Radiation Modes:**

1	HDMI+DP Mode 1920X1080, VF=60Hz	120VAC, 60Hz
2	HDMI+DP Mode 1920X1080, VF=60Hz	230VAC, 60Hz
	HDMI+DP Mode 1920X1080, VF=60Hz / 1-18GHz	

**Worst:**

**Conduction:** Mode 2

**Radiation:** Mode 2

#### 3.2. EUT SYSTEM OPERATION

1. Windows 10 boots system.
2. Run Emctest.exe to activate all peripherals and display "H" pattern on monitor screen.
3. Run Winemc.exe and choose media player to play music.
4. Run Winemc.exe then select (E:/ & F:/) to test EUT.
5. Press the start menu, select executive and type ping 192.168.1.1&2-t (EUT), ping 192.168.1.10&20-t (Sever PC).

**Note:** Test program is self-repeating throughout the test.

## 4 SETUP OF EQUIPMENT UNDER TEST

### 4.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

#### EUT Devices:

No.	Equipment	Model No.	Brand Name
1	CPU (4.40GHz)	Intel® Core i7-8665UE	Intel
2	Memory (DDR4 2400MHz 8GB) *2	Hynix H5ANAG6NAMR-UHC	N/A
3	Power Adapter	GEO651DA-190342	GEAO
4	SATA HDD (500GB)	MQ01ABF050	TOSHIBA

#### Peripherals Devices:


No.	Equipment	Model No.	Serial No.	FCC ID / BSMI ID	Brand Name	Data Cable	Power Cord
1	Earphone	X710	N/A	N/A	HAWK	Unshielded, 1.8m	N/A
2	USB Mouse	M-U0026	N/A	BSMI: T41126	Logitech	Shielded, 1.8m	N/A
3	USB Keyboard	Y-U0009	N/A	BSMI: D51160	Logitech	Shielded, 1.8m	N/A
4	Monitor	PA248Q	G5LMQS071284	BSMI: R31018	ASUS	Shielded, 1.8m	Unshielded, 1.8m
5-6	USB HDD	TS1TSJ25MC	E57223-0006	BSMI: D33193	Transcend	Shielded, 0.6m	N/A
7-8	Modem	AL-56ERM	0MERM04A0212	DOC	GALILEO	Shielded, 1.8m	Unshielded, 1.8m with a core
9	Monitor	PA248Q	G5LMQS071275	BSMI: R31018	ASUS	Shielded, 1.8m	Unshielded, 1.8m
10	Server PC	T5810	2H7XZG2	DOC BSMI: R33002	DELL	Unshielded, 20m	Unshielded, 1.8m
11	Server PC	T5810	2H6YZG2	DOC BSMI: R33002	DELL	Unshielded, 20m	Unshielded, 1.8m

#### Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



## 4.2. CONFIGURATION OF SYSTEM UNDER TEST



## 5 FACILITIES AND ACCREDITATIONS

### 5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at CCSrf Taiwan Xindian Lab. at No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, 23151 Taiwan.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

### 5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
USA	A2LA

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Japan	VCCI
Taiwan	BSMI
USA	FCC

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

### 5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	0.15MHz ~ 30MHz	± 2.76
Radiated emissions	30MHz ~ 1000MHz	± 5.24
	1000MHz ~ 18000MHz	± 4.69
	18000MHz ~ 40000MHz	± 4.12

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22: 2005, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than  $U_{CISPR}$  which is 3.4dB(AMN) and 6.3dB(OATS) respectively. CCS values (called  $U_{Lab}$  in CISPR 16-4-2) is less than  $U_{CISPR}$  as shown in the table above. Therefore, MU need not be considered for compliance.

## 6 CONDUCTED EMISSION MEASUREMENT

### 6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

**NOTE:**

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 6.2. TEST INSTRUMENTS

Conducted Emission room # A				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Attenuator	EMEC	EM-ATT-3000-10-005-BB	SD-C011	03/25/2020
BNC CABLE	EMEC	EMG178	BNC#A9	03/25/2020
EMI Test Receiver	R&S	ESCI	101201	09/17/2020
LISN	Schwarzbeck	NNLK 8129	8129-286	08/11/2020
LISN(EUT)	Schwarzbeck	NSLK 8127	8127527	08/06/2020
Thermo-Hygro Meter	Wisewind	201A	No. 02	04/29/2020
Test S/W	EZ-EMC			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. N.C.R = No Calibration Request.

### 6.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)


#### Procedure of Preliminary Test

- The EUT and support equipment, if needed, were set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- The test equipment EUT installed by AC 120VAC/60Hz main power, through a Line Impedance Stabilization Network (LISN), which was supplied power source and was grounded to the ground plane.
- All support equipment power by from a second LISN.
- The test program of the EUT was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

#### Procedure of Final Test

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- The test data of the worst-case condition(s) was recorded.

## 6.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 6.5. DATA SAMPLE

Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
x.xx	42.95	0.55	43.50	73	-29.50	Q	L1


Freq.	= Emission frequency in MHz
Reading	= Uncorrected Analyzer/Receiver reading
Factor	= Insertion loss of LISN + Cable Loss + Pulse Limit
Result	= Reading + Factor
Limit	= Limit stated in standard
Margin	= Reading in reference to limit
P	= Peak Reading
Q	= Quasi-peak Reading
A	= Average Reading
L1	= Hot side
L2	= Neutral side

### Calculation Formula

$$\text{Margin (dB)} = \text{Result (dBuV)} - \text{Limit (dBuV)}$$

## 6.6. TEST RESULTS


Model No.	UPX-WHL01; UPX-EDGE; PER-TAIX2-A20-2280	6dB Bandwidth	9 kHz
Environmental Conditions	22°C, 61% RH	Test Mode	Mode 2
Tested by	Jacky Lin	Phase	L1
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1700	52.77	10.07	62.84	79.00	-16.16	P	L1
0.5020	32.42	10.10	42.52	73.00	-30.48	P	L1
2.2340	34.60	10.27	44.87	73.00	-28.13	P	L1
5.1779	39.47	10.41	49.88	73.00	-23.12	P	L1
14.9060	37.37	10.75	48.12	73.00	-24.88	P	L1
28.2140	34.35	11.14	45.49	73.00	-27.51	P	L1

Note: L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Model No.	UPX-WHL01; UPX-EDGE; PER-TAIX2-A20-2280	6dB Bandwidth	9 kHz
Environmental Conditions	22°C, 61% RH	Test Mode	Mode 2
Tested by	Jacky Lin	Phase	L2
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1660	52.02	10.07	62.09	79.00	-16.91	P	L2
0.4500	33.87	10.09	43.96	79.00	-35.04	P	L2
0.9860	33.89	10.15	44.04	73.00	-28.96	P	L2
5.1300	42.27	10.38	52.65	73.00	-20.35	P	L2
14.1060	33.42	10.71	44.13	73.00	-28.87	P	L2
29.5820	33.68	11.23	44.91	73.00	-28.09	P	L2

**Note:** L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

## 7 RADIATED EMISSION MEASUREMENT

### 7.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Below 1GHz (for digital device)

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHZ)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

**NOTE:** (1) The lower limit shall apply at the transition frequencies.  
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).  
 (3) The measurement above 1GHz is at close-in distances 3m, and determine the limit  $L_2$  corresponding to the close-in distance  $d_2$  by applying the following relation:  $L_2 = L_1 (d_1/d_2)$ , where  $L_1$  is the specified limit in microvolts per metre (uV/m) at the distance  $d_1$  (10m),  $L_2$  is the new limit for distance  $d_2$  (3m).  
 So the new Class A limit above 1GHz at 3m is as following table:

Frequency (MHZ)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80



According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40GHz, whichever is lower

## 7.2. TEST INSTRUMENTS

Open Area Test Site # H				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Bilog Antenna	Teseq	CBL 6112D	40529	08/29/2020
Cable	EMEC	CFD400NL-LW	N-Type#H11	08/14/2020
EMI Test Receiver	R&S	ESCI	101340	03/19/2020
Pre-Amplifier	HP	8447D	1937A01554	09/26/2020
Thermo-Hygro Meter	Wisewind	201A	No. 03	05/21/2020
Test S/W	EZ-EMC			
Above 1GHz Used				
Horn Antenna	ETS	3117	00139062	08/07/2020
K-Type Cable x 1m (1-40GHz)	Rosnol	K1K50-UP0264- K1k50-1M	160215-1	11/26/2019
Microflex Cable x 7m (1-18GHz)	Rosnol	A1K50-EW0630- A1k50-700CM	SD-R028	11/26/2019
Pre-Amplifier	HP	8449B	3008A01266	11/25/2019
Signal Analyzer	Agilent	N9010A	MY53440125	12/25/2019
Thermo-Hygro Meter	Wisewind	N/A	SD-R027	09/17/2020
Test S/W	EZ-EMC			

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. N.C.R = No Calibration Request.

### 7.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)

#### **Procedure of Preliminary Test**


- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC 120VAC/60Hz power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

#### **Procedure of Final Test**


- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 or 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.

## 7.4. TEST SETUP

### Below 1GHz



### Above 1GHz



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 7.5. DATA SAMPLE

### Below 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/Q)	Pol. (H/V)
x.xx	14.0	12.2	26.2	40	-13.8	Q	H

### Above 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
x.xx	42.95	0.55	43.50	60	-16.50	A	H

Freq. = Emission frequency in MHz  
 Reading = Uncorrected Analyzer/Receiver reading  
 Factor = Antenna Factor + Cable Loss - Amplifier Gain  
 Result = Reading + Factor  
 Limit = Limit stated in standard  
 Margin = Reading in reference to limit  
 P = Peak Reading  
 Q = Quasi-peak Reading  
 A = Average Reading  
 H = Antenna Polarization: Horizontal  
 V = Antenna Polarization: Vertical


### Calculation Formula

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

## 7.6. TEST RESULTS

### Below 1GHz


<b>Model No.</b>	UPX-WHL01; UPX-EDGE; PER-TAIX2-A20-2280	<b>Test Mode</b>	Mode 2
<b>Environmental Conditions</b>	22°C, 65% RH	<b>6dB Bandwidth</b>	120 kHz
<b>Antenna Pole</b>	Vertical	<b>Antenna Distance</b>	10m
<b>Detector Function</b>	Quasi-peak.	<b>Tested by</b>	Jacky Lin
<b>Standard</b>	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		



Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
73.4200	48.20	-14.02	34.18	40.00	-5.82	100	136	Q	V
94.8900	44.30	-10.23	34.07	40.00	-5.93	100	299	Q	V
109.3100	37.60	-8.29	29.31	40.00	-10.69	100	140	Q	V
165.3900	42.80	-9.69	33.11	40.00	-6.89	100	255	Q	V
208.5399	39.70	-10.02	29.68	40.00	-10.32	100	113	Q	V
220.1100	37.60	-9.92	27.68	40.00	-12.32	100	250	Q	V

**Note:** 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.  
2. P= Peak Reading; Q= Quasi-peak Reading.

Model No.	UPX-WHL01; UPX-EDGE; PER-TAIX2-A20-2280	Test Mode	Mode 2
Environmental Conditions	22°C, 65% RH	6dB Bandwidth	120 kHz
Antenna Pole	Horizontal	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Jacky Lin
Standard	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		



Radiated Emission Readings									
Frequency Range Investigated				30 MHz to 1000 MHz at 10m					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
70.4200	39.50	-14.06	25.44	40.00	-14.56	400	65	Q	H
105.5700	35.80	-8.54	27.26	40.00	-12.74	400	119	Q	H
154.6200	35.60	-9.27	26.33	40.00	-13.67	400	282	Q	H
173.8100	39.30	-9.93	29.37	40.00	-10.63	400	121	Q	H
209.3500	37.80	-10.04	27.76	40.00	-12.24	400	137	Q	H
233.6800	39.70	-8.43	31.27	47.00	-15.73	400	44	Q	H

**Note:** 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.  
2. P= Peak Reading; Q= Quasi-peak Reading.

### Above 1GHz

<b>Model No.</b>	UPX-WHL01; UPX-EDGE; PER-TAIX2-A20-2280	<b>Test Mode</b>	Mode 2
<b>Environmental Conditions</b>	23°C, 61% RH	<b>6dB Bandwidth</b>	1 MHz
<b>Antenna Pole</b>	Vertical / Horizontal	<b>Antenna Distance</b>	3m
<b>Highest frequency generated or used</b>	4400MHz	<b>Upper frequency</b>	18000MHz
<b>Detector Function</b>	Peak and average.	<b>Tested by</b>	Jacky Lin
<b>Standard</b>	FCC CLASS A		



Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1311.667	54.07	-6.74	47.33	80.00	-32.67	P	V
1850.000	52.37	-2.80	49.57	80.00	-30.43	P	V
2983.333	52.25	-1.60	50.65	80.00	-29.35	P	V
3691.667	49.86	-0.49	49.37	80.00	-30.63	P	V
4995.000	54.10	1.38	55.48	80.00	-24.52	P	V
5986.667	50.72	2.63	53.35	80.00	-26.65	P	V

Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1085.000	58.38	-6.63	51.75	80.00	-28.25	P	H
1368.333	55.05	-6.44	48.61	80.00	-31.39	P	H
1991.667	53.07	-2.86	50.21	80.00	-29.79	P	H
2445.000	52.19	-2.52	49.67	80.00	-30.33	P	H
3011.667	52.28	-1.48	50.80	80.00	-29.20	P	H
4995.000	48.94	1.38	50.32	80.00	-29.68	P	H

**Note:** 1. P= Peak Reading; A= Average Reading.



## 8 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST





**RADIATED EMISSION TEST**